



Home > Equipment > Mini Skid Steers > S400TX

S400TX Specs

| General Dimensions and Weights | | |
|---|---------------------|-----------|
| Design | Ride-on/track drive | |
| Length with Standard Bucket | 96.5" | 245.11 cm |
| Length without Standard Bucket | 76.5" | 194.31 cm |
| Width with Standard Bucket | 42" | 106.68 cm |
| Width Without Standard Bucket | 34.5" | 87.63 cm |
| Height | 49" | 124.46 cm |
| Height (to Hinge Pin) | 69" | 175.26 cm |
| Ground Clearance | 6" | 15.24 cm |
| Weight (Standard Bucket, Gas Engine) | 2119 lbs | 961.16 kg |
| Weight (No Bucket, Gas Engine) | 1950 lbs | 884.51 kg |

| Engine Option One | | |
|---------------------------|----------------------|----------|
| Make and Model | Kohler Command CH730 | |
| Fuel Type | Gas | |
| Fuel Tank Capacity | 7.5 gal | 28.43 L |
| Gross Horsepower | 23 hp | 17.15 kw |
| Cooling System | Air | |

Track Performance

| | | |
|---|----------|------------------|
| Rated Operating Capacity (SAE) | 500 lbs | 226.8 kg |
| Tipping Capacity (With 175 lb (79.38 kg) operator) | 1430 lbs | 648.64 kg |
| Travel Speed | 3.9 mph | 6.28 km/h |
| Ground Pressure (Narrow Tracks) | 3.8 psi | 26.200077664 kPa |
| Ground Pressure (Wide Tracks) | 3 psi | 20.68427184 kPa |

Operational

| | | |
|---------------------|--|--|
| Steering | Standard mechanical dual axis joystick | |
| Lift | Single dual-axis joystick | |
| Curl | Single dual-axis joystick | |
| Transmission | Dual-Piston Hydraulic pumps | |

Hydraulic System

| | | |
|----------------------------------|----------|-------------|
| Hydraulic System Flow | 11.5 gpm | 43.59 L/min |
| Hydraulic System Pressure | 2650 psi | 182.71 bar |
| Tank capacity | 8 gal | 30.28 L |

ATTACHMENTS

Copyright © 2010. Vermeer Corporation. All Rights Reserved.

www.vermeer.com